

## DECLARATION OF PERFORMANCE

No. BPL 3W 01/08/2015

1. Unique identification code of the product-type:

**BC1, BC4, BC8, BG1, BG2, BG4, BK1, BK2, BK3, BK4, BK6, BK8, BK9, BKT, BKW**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
**Production code is indicated on the bottom side of each board.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Three-layer floor board, designed to be laid on floors in apartments in the system of floating floor assembly; installation by gluing it to the base floor; and in the system of electric and water floor heating solution. The product is covered with finishing varnish or with oil.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Three-layer floor board  
 Barlinek Inwestycje Sp. z o. o.  
 Przemysłowa 1, 74-320 Barlinek**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
**not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Institute of Wood Technology in Poznań, Winiarska 1; 60-654 Poznań, the laboratory's notification number – 1583**

**and Building Research Institute in Warsaw, Filtrowa 1; 00-611 Warszawa, the laboratory's notification number – 1488**

performed **type tests** under system **3** and issued test reports.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**not applicable**


9. Declared performance

Essential characteristics	Declared performance	Harmonised standard
Reaction to fire	D <sub>fl</sub> – s1	EN 14342:2013
Minimal density	500 kg/m <sup>3</sup>	
Minimal thickness	10mm	
Release of formaldehyde	E-1	
Content of pentachlorophenol	≤5ppm	
Thermal conductivity	0,14W/mK	
Slipperiness	NPD	
Biological durability	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
 Signed for and on behalf of the manufacturer by:

..... Piotr Hoffmann, R&D Director  
 (name and function)

..... Barlinek, 18.08.2015  
 (place and date of issue)

  
 (signature)